













Polyflex Plus


Polyflex Plus PU is a durable, general purpose vinyl tile suitable for most contract situations. The excellent performance makes Polyflex Plus PU a good choice in schools, supermarkets and offices. The excellent performance of Polyflex Plus makes it a particularly suitable and economical solution for social housing refurbishment projects. With excellent durability, ease of maintenance and endless design possibilities, Polyflex Plus provides the ideal flooring solution to complement any interior design scheme.




	Gauge	ISO 24346 (EN 428)	2.0mm
	Tile Size	ISO 24342 (EN 427)	2.0mm: 300 x 300mm = 4.5m ²
	Total Weight	ISO 23997 (EN 430)	2.0mm: 3800g/m ²
	General Performance	ISO 10581 (EN 649)	Conforms
	Use Area	ISO 10874 (EN 685)	
	Reaction to Fire	EN 13501-1 ASTM E648	Class Bfl-S1 Class 1
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Slip Resistance	EN 13893	Class DS
	Residual Indentation	ISO 24343-1 (EN 433)	<0.10mm
	Dimensional Stability	ISO 23999 (EN 434)	<0.25%
	Flexibility	ISO 24344 (EN 435)	(Method A) Pass 40mm mandrel
	VOC Emissions	Indoor Air Comfort GOLD AgBB/ABG	Eurofins certified product Pass

Environmentally Preferable Flooring - Polyflex Plus PU achieves a BRE Global Environmental Generic A+ rating. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflex Plus PU is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability

PU - Polyflex Plus PU features a polyurethane surface treatment which provides an excellent foundation for an easy, ongoing maintenance regime.

 For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. **Decoration and shade may vary slightly from the samples shown.**



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 | email: info@polyflor.com | www.polyflor.com

