





















CAMARO™

Camaro is a collection of luxury vinyl tiles featuring small and large parquet as well as wood and stone designs. Common use areas for Camaro include mainly residential or light commercial.



	Gauge	ISO 24346 (EN 428)	2.0mm
	Wear Layer	ISO 24340 (EN 429)	0.30mm
	Plank Size	ISO 24342 (EN 427)	192 @ 76.2 x 228.6mm = 3.34m ² 96 @ 76.2 x 457.2mm = 3.34m ² 36 @ 101.6 x 914.4mm = 3.34m ² 24 @ 152.4 x 914.4mm = 3.34m ² 18 @ 152.4 x 1219.2mm = 3.34m ² 15 @ 184.2 x 1219.2mm = 3.37m ² 12 x 3 @ 76.2 / 101.6 / 152.4 x 914.4mm = 3.62m ²
	Tile Size	ISO 24342 (EN 427)	36 @ 304.8 x 304.8mm = 3.34m ² 18 @ 304.8 x 609.6mm = 3.34m ²
	Total Weight	ISO 23997 (EN 430)	3600g/m ²
	General Performance	ISO 10582 (EN 649)	Conforms
	Use Area	ISO 10874 (EN 685)	
	Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586	Class DS R10 R10
For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.			
	Binder Content	ISO 10582	Type I
	Abrasion Resistance	EN 649	Group T
	Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 <450 Pass Class 1 FSV < 300; SDV < 500
	Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
	Residual Indentation	ISO 24343-1 (EN 433)	<0.05mm
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	Dimensional Stability	ISO 23999 (EN 434)	≤0.10% max
	Underfloor Heating		Suitable, max 27°C
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	VOC Emissions	REAcH Indoor Air Comfort GOLD FloorScore FinnishM1 AgBB/ABG	Compliant Eurofins certified product Certified Certified Pass
	Responsible Sourcing	BES 6001 SA 8000	Very Good Approved factory


Environmentally Preferable Flooring - Polyflor Camaro PUR achieves BRE Global A+ rating (ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Polyflor Camaro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com**.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.



BS EN 14041 EN 14041



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 | email: info@polyflor.com | www.polyflor.com

