



INITIAL CONSTRUCTION CLEAN

After installation, wait 48 hours before proceeding with the construction/intensive clean.

- Sweep or dry vacuum the floor to remove dust, grit and debris.
- Apply a solution of alkaline cleanser, diluted as per the manufacturer's instructions, to the floor and leave for at least 5 minutes (or longer if manufacturer recommends) to react, before proceeding. Using a 150 to 175 rpm rotary machine fitted with suitable brushes, machine scrub the floor and then pick up the slurry with a mop or wet vacuum.
- The floor should then be rinsed with clean water and allowed to dry.



APPLICATION OF A FLOOR DRESSING

- Prior to the application of a floor dressing, ensure that the floor is completely stripped, clean and free from any contaminants. This will ensure that there is a good key between the dressing and the surface of the floor.
- Apply two or three thin coats of emulsion polish in accordance with the manufacturer's instructions, with either a proprietary polish applicator or Kentucky mop wrung out to prevent over-application of polish. The polish should be applied up to 150mm from the edges of the room and subsequent coats should be applied at 90° to the previous one. The final coat should be applied right up to the edges of the room.



ROUTINE MAINTENANCE

- The frequency of each of the operations is dependent upon the type and intensity of the traffic.
- Firstly, sweep or dry vacuum daily to remove dust and loose dirt.
- Secondly, spot mop frequently. Rinse the area with clean warm water and allow to dry.
- Thirdly, as required, and normally at least once per week, use a floor maintainer, diluted as per the manufacturer's instructions. Mop the floor and leave to dry. If a shine is required, the floor should be buffed with a 300 to 500 rpm rotary machine fitted with suitable fibre or nylon brushes.
- Regular buffing of SaarFloor-Systems Rubber Sheet and Tile will enhance its appearance.



REMOVAL OF FLOOR DRESSING

- An unsightly build-up of polish should be avoided. The polish should be removed regularly, the interval between application and removal depends on the wear conditions and the number of polish layers. (Normally six months in heavy traffic areas.)
- Apply a solution of emulsion polish stripper, diluted to the manufacturer's instructions, to the floor and leave for approximately 15 minutes. Machine scrub with a 150 to 175 rpm machine fitted with a suitable brush and then remove slurry with a wet vacuum. Thoroughly rinse the floor with clean warm water, pick up with a wet vacuum and allow to dry completely. The cycle of polish application and routine maintenance should then be repeated.



- For further guidance, contact Polyflor Customer Technical Support. Always follow the Health and Safety guidance provided.
REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.



SaarFloor
Systems

RUBBER SHEET AND TILE

FLOORCARE

APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

PRODUCT	NEUTRAL CLEANSER	ALKALINE CLEANSER	MAINTAINER/WASH & WAX	FLOOR POLISH	POLISH STRIPPER	POWER CLEANER (Spot Cleaner)
DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	Active Cleaner	Clean and Strip	Floor Cleaner R1000	Floor Shine Floor Mat Secura Hard Sealer	Clean & Strip	Turbo Strip
BRITISH NOVA Tel: 01295 251721 www.cleenol.co.uk	Liquid 99	Novaways Nova Multi Purpose Sanitiser Nova Safety Floor Cleaner	Novacare	Nova Long Life Gloss Nova Long Life Satin	Nova Starbrite	Nova Multi Purpose Sanitiser
PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	Natural Multi Surface Floor Cleaner	Alkleen Ultrapac Renovate Powerclean	Protreat	Proshine	Prostrip	Powerclean
EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	High Class	E.M.C Plus Versatile Lift	Clean & Shine	Sustain Mexapol Enhance	Easystrip Sure Strip	Lift
ECOLAB LTD Tel: 01793511221 www.ecolab.com	Maxx Brial 2 Neomax Star Plus	Regain Neomax GMS Maxx Magic 2	Indur XL Fresh Indur Brilliant Plus Maxx Indur 2	Isi Star Maxx Isi 2 Tuklar Maxx	Maxx Bendurol 2 Maxx Forte2l	Pep Active
DIVERSEY UK LTD Tel: 01604405311 www.diversey.com	Taski Jontec 300 Carefree Stride 1000	Carefree Stride 2000 Taski Jontec Forward	Carefree Stride 3000 Taski Jontec Tensol	Carefree Eternum Taski Jontec Eternum	Carefree Stripper Carefree Speed Stripper	Taski Sprint Spitfire
SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk	Frequent Use Scrubber Drier Detergent Sabre	Multi-Purpose Cleaner Selclen S Triple	Selsheen Fast Lane Low Foam Floor Maintainer	Seldur Selexel Diamond Brite	Selstrip Selspeed Selate	Maxima
PREMIERE PRODUCTS Tel: 01298 28505 www.premiereproducts.co.uk	Low Foam	MP9 MP10	Clean & Buff GC10	Platinum 25 Premac Super	Premstrip	Force

CHEMICAL FREE CLEANING	HOMOGENEOUS		POLYSAFE APEX POLYSAFE ULTIMA
	HETEROGENEOUS LUXURY VINYL TILES	SAFETY	
DECITEX Tel: www.	Decitex Disposable Machine washable (various)	Decitex Ultimate Dx1 Dx1 Ultimate Duo-White M800	Decitex Ultimate Duo-White

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.